

2019-04-18

HMS83 Outdoor Humidity and Temperature Transmitter for Building Automation



Features/Benefits:

- Reliable transmitters for basic HVAC humidity measurements
- ± 3.0 %RH accuracy
- User exchangeable INTERCAP® sensor for easy field replacement
- Output parameters: relative humidity and temperature with optional dewpoint temperature, wet bulb temperature and enthalpy
- Shield protects temperature and humidity probes from scattered, as well as, direct solar radiation and rain
- Easy to install on a pole, horizontal beam or flat surface

Summary:

Outdoor mounted transmitter shall incorporate a thin film polymer capacitive INTERCAP® relative humidity sensor. Sensor is calibration free. Electronics to be protected in a NEMA4 enclosure. Transmitter probe integrated a naturally aspirated solar radiation and precipitation shield. Accuracy is $\pm 3\%$ RH from 0 and 90% RH and $\pm 5\%$ from 90 to 100% RH between $+10 \dots +30$ °C ($+50 \dots +86$ °F). Sensor to have a stability of $\pm 2\%$ RH over a two year period. Transmitter shall operate over a humidity range of 0...100%. Transmitter to be powered by 18...35VDC or 24 VAC and provide a linear output signal of 0...10V corresponding to 0 to 100% RH. Temperature sensor shall be a platinum 1000 Ω RTD with a linear output of 0...10V corresponding to -40° to $+60^{\circ}$ C (-40° to $+140^{\circ}$ F) with an accuracy of $\pm 0.3^{\circ}$ C (0.54° F) at 20° C (68° F). Shall have options to calculate and output additional parameters: dew point temperature, wet bulb temperature, and enthalpy.

Vaisala Model: HMS83 (Relative Humidity and Temperature)

Vaisala Model: HMS83C (Relative Humidity and Temperature with NPT 1/2" conduit fitting)